

GAS HOSE

Connection:	Pivot: Aluminu	m Connectior	n <u>: Brass</u> F	erule:Aluminum	
Work Temperature:	<u>140°F</u>				
Work Pressure 350 psi					
Diameter <u>5/16</u>					
Guarantee: <u>3 years</u>	Unit / Packing	Max. Stowage	Packing		
Tissue: <u>Aluminum</u>	<u>25</u>	<u>5</u>	<u>Bag</u>		
Presentations:				_	

Code	Lenght Cm	Connction
GA.5/16.60	60	3/8" x 3/8"
GA.5/16.1	100	3/8" x 3/8"
GA.5/16.1.5	150	3/8" x 3/8"
GA.5/16.2	200	3/8" x 3/8"
GA.5/16.3	300	3/8" x 3/8"
GA.5/16.4	400	3/8" x 3/8"
GA.5/16.5	500	3/8" x 3/8"
GA.5/16.10	1000	3/8" x 3/8"

Installing recomentations

Observations:

Guarantee only apply in manufactring defects

1 Shut off

- 2 Make sure the connections are clean
- **3** Do not use tape
- 4 put with your hands and then tighten with tools
- 5 Verify with soapy water there is no leaks
- 6 Avoit contact with fire, chemicals and cor

Corporativo Boro S.A. de C.V Tel: (0133) 3834 0659 • Lada: 01800 700 BORO (2676) Las Lomas 144 • Fracc. Los Robles • C.P. 45134 Zapopan, Jalisco, México



